



Product Service

CERTIFICATE

No. Z1 18 07 12881 282

Holder of Certificate: **Zarges GmbH**

Zargesstr.7
82362 Weilheim
GERMANY

Production
Facility(ies):

36773

Certification Mark:



Product:

**Standing step ladders
Z600**

Model(s):

41223 / 41224 / 41225
41226 / 41227 / 41228
41230
41090 / 5410901 / 5410903
41091 / 5410911 / 5410913
41092 / 5410921 / 5410923 / 5410924
41093 / 5410931
41094 / 5410941
41095 / 5410951
41098 / 5410961

Parameters:

max. load: 150 kg

further parameter see attachment 1.

Tested according to:

DIN EN 131-1:2016
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-03:2017

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.:

028-713102252-046

Valid until:

2023-07-10

Date, 2018-07-12


(Michael Heufelder)

Page 1 of 2





Parameter – standing step ladders Z600

Z600	standing step ladders with platform and handrail, for professional use;	
max. load :	150 kg	
art-no.	no. of steps	max. standing height
41223:	1 x 3	665 mm
41224:	1 x 4	885 mm
41225:	1 x 5	1105 mm
41226:	1 x 6	1325 mm
41227:	1 x 7	1546 mm
41228:	1 x 8	1766 mm
41230:	1 x 10	2206 mm
climbing side	stiles	steps
41223-26:	42 x 25 x 1,2 mm	80 x 35 x 1,3 mm
41227-30:	48 x 25 x 1,5 mm	
supporting side:	42 x 25 x 1,2 mm	
Material:	EN AW 6060	EN AW 6061
Z600	standing step ladders with platform XL and handrail, for professional use;	
max. load :	150 kg	
art-no.	no. of steps	max. standing height
41090 / 5410901 / 5410903:	1 x 3	740 mm
41091 / 5410911 / 5410913:	1 x 4	990 mm
41092 / 5410921 / 5410923 / 5410924:	1 x 5	1240 mm
41093 / 5410931:	1 x 6	1490 mm
41094 / 5410941:	1 x 7	1740 mm
41095 / 5410951:	1 x 8	1990 mm
41098 / 5410961:	1 x 10	2490 mm
climbing side	stiles	steps
41090-92 / 5410901-21 / 5410903-24:	42 x 25 x 1,2 mm	80 x 35 x 1,3 mm
41093-98 / 5410931-61:	48 x 25 x 1,5 mm	
supporting side:	42 x 25 x 1,2 mm	
Material:	EN AW 6060	EN AW 6061

Munich, 2018-07-12